



T760AA Series

75 PSI Light Weight Dry Powder Delivery Hose

GENERAL APPLICATIONS

- Discharge of dry powders under low pressure, such as dry cement, grains and animal feed transfer

CONSTRUCTION

Tube – 3/16" black static conducting NR – compounded to resist cutting by abrasive materials

Reinforcement – Spiraled high tensile textile cords

Cover – Black conductive SBR/NR blend – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 5 Bar (75 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 760 5 BAR (75 PSI) BULK MATERIAL DELIVERY (in white letters)

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
T760AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T760AA400	4	102	4.53	115	75	100	1.58
T760AA450	4 1/2	115	5.00	127	75	100	1.85
T760AA500	5	127	5.47	139	75	100	2.05
T760AA600	6	152	6.61	168	75	100	2.30

NOTES:

ⓘ Excessive bending during operation may cause premature wear.

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.