



HWT763AA Series

75 PSI Heavy Duty Dry Powder Delivery Hose 3/8" Tube

GENERAL APPLICATIONS

- Discharge of dry powders under low pressure
- Pneumatic transfer of dry materials and abrasive slurries

CONSTRUCTION

Tube – 3/8" black static conducting NR – compounded to resist cutting by abrasive materials

Reinforcement – Spiraled high tensile textile cords

Cover – Black conductive SBR/NR blend – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 5 Bar (75 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY HWT 763 5 BAR (75 PSI) HEAVY DUTY BULK MATERIAL DELIVERY (in green letters)

View Up To Date Info



← SCAN OR VISIT
[KOA.link/
HWT763AA](https://koa.link/HWT763AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
HWT763AA400	4	102	4.96	126	75	100	2.56

NOTES:

ⓘ Excessive bending during operation may cause premature wear.

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://koa.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.