



## T766AA Series

### 150 PSI Heavy Duty Dry Powder Delivery Hose

#### GENERAL APPLICATIONS

- Discharge of dry powders in heavy duty applications, such as dry cement, grains and animal feed transfer

#### CONSTRUCTION

**Tube** – 1/4" black static conducting NR – compounded to resist cutting by abrasive materials

**Reinforcement** – Spiraled high tensile textile cords

**Cover** – Black conductive SBR/NR blend – abrasion and ozone resistant

#### WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 766 10 Bar (150 PSI) BULK MATERIAL DELIVERY (in white letters)

View Up To Date Info



← SCAN OR VISIT

[KOA.link/T766AA](https://KOA.link/T766AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(in)			
T766AA400	4	102	4.65	118	150	100	1.96

**NOTES:**

ⓘ Excessive bending during operation may cause premature wear.

**COUPLING SUGGESTIONS:** Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

**i** Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.