



T966AA Series

Cable Protection Hose MSHA Approved

GENERAL APPLICATIONS

- Cable protection in underground mining operations
- Suitable for light duty air and water applications up to 75 psi working pressures

CONSTRUCTION

Tube – Black conductive SBR/NR blend

Reinforcement – High tensile textile cords with 4 spiral reinforcement.

Cover – Black conductive SBR compounds providing abrasion, ozone and flame resistance

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176 °F (+80°C)

BRANDING

ALFAGOMMA ITALY 966 CABLE COVER MSHA 2G-1C-62C/01 5 bar (75 psi) (in orange letters)

View Up To Date Info



← SCAN OR VISIT
[KOA.link/
T966AA](https://KOA.link/T966AA)

FEATURES AND ADVANTAGES

- Comprehensive Size Range - Nine available sizes to accommodate a wide range of hose and cable sizes.
- MSHA Accepted - Hose is accepted as having met the Interim Fire Criteria Acceptance of Products Taken Into Underground Mines per MSHA 2G-1C-62C/01.
- Meets part 18 Flame-Resistant hose conduit MSHA

Series Number	ID		OD		Max. Working Pressure (psi)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)				
T966AA050	1/2	13	0.91	23	75	4	100	0.17
T966AA062	5/8	16	1.10	28	75	5	100	0.19
T966AA075	3/4	19	1.22	31	75	6	100	0.28
T966AA100	1	25	1.45	37	75	8	100	0.35
T966AA125	1 1/4	32	1.73	44	75	10	100	0.43
T966AA150	1 1/2	38	1.97	50	75	15	100	0.50
T966AA175	1 3/4	45	2.34	57	75	18	100	0.58
T966AA200	2	51	2.40	61	75	20	100	0.65
T966AA250	2 1/2	63	2.87	73	75	25	100	0.82

COUPLING SUGGESTIONS: Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.