



## T352AA Series

### 75 PSI Radiator Hose

#### GENERAL APPLICATIONS

- Radiator hose

#### CONSTRUCTION

Tube – Black EPDM

Reinforcement – Two ply, high tensile textile cords – 2 ply all sizes. Not for vacuum

Cover – Black EPDM – heat, abrasion and ozone resistant

#### WORKING PRESSURE

Constant Pressure –  
5 Bar (75 PSI)

#### SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +248°F (+120°C)

#### BRANDING

ALFAGOMMA – ITALY – 352 RADIATOR – DIN 73411 – dia mm / in. SAE 20R1-D2 (in yellow letters)

View Up To Date Info



◀ SCAN OR VISIT

[KOA.link/  
T352AA](http://KOA.link/T352AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length Coils (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T352AA050X12.6	1/2	13	0.83	21	75	12'6"	0.19
T352AA050X200	1/2	13	0.83	21	75	200'	0.19
T352AA062X12.6	5/8	16	0.94	24	75	12'6"	0.22
T352AA071X12.6	23/32	18	1.02	26	75	12'6"	0.24
T352AA078X12.6	13/16	20	1.10	28	75	12'6"	0.26
T352AA087X12.6	7/8	22	1.18	30	75	12'6"	0.28
T352AA087X200	7/8	22	1.18	30	75	200'	0.28
T352AA100X12.6	1	25	1.30	33	75	12'6"	0.32
T352AA100X200	1	25	1.30	33	75	200'	0.32
T352AA112X12.6	1 1/8	28	1.42	36	75	12'6"	0.34
T352AA112X200	1 1/8	28	1.42	36	75	200'	0.34
T352AA118X12.6	1 3/16	30	1.50	38	75	12'6"	0.37
T352AA125X12.6	1 1/4	32	1.57	40	75	12'6"	0.39
T352AA125X200	1 1/4	32	1.57	40	75	200'	0.39

See additional sizes...

**i** Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](http://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



## T352AA Series

75 PSI Radiator Hose

*(continued from previous page)*

View Up To Date Info



◀ SCAN OR VISIT  
**KOA.link/  
T352AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length Coils (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T352AA137X12.6	1 3/8	35	1.69	43	75	12'6"	0.42
T352AA150X12.6	1 1/2	38	1.89	48	75	12'6"	0.57
T352AA150X200	1 1/2	38	1.89	48	75	200'	0.57
T352AA162X12.6	1 5/8	42	2.05	52	75	12'6"	0.63
T352AA162X200	1 5/8	42	2.05	52	75	200'	0.63
T352AA175X12.6	1 3/4	45	2.17	55	75	12'6"	0.66
T352AA175X200	1 3/4	45	2.17	55	75	200'	0.66
T352AA189X12.6	1 7/8	48	2.28	58	75	12'6"	0.70
T352AA189X200	1 7/8	48	2.28	58	75	200'	0.70
T352AA200X12.6	2	51	2.40	61	75	12'6"	0.75
T352AA200X200	2	51	2.40	61	75	200'	0.75
T352AA225X12.6	2 1/4	57	2.64	67	75	12'6"	0.82
T352AA238X12.6	2 3/8	60	2.76	70	75	12'6"	0.86
T352AA250X12.6	2 1/2	63	2.87	73	75	12'6"	0.90
T352AA275X12.6	2 3/4	70	3.15	80	75	12'6"	0.97
T352AA300X12.6	3	76	3.39	86	75	12'6"	1.04
T352AA315X12.6	3 1/8	80	3.54	90	75	12'6"	1.10
T352AA354X12.6	3 9/16	90	4.02	102	75	12'6"	1.36
T352AA400X12.6	4	102	4.49	114	75	12'6"	1.52
T352AA450X12.6	4 1/2	116	5.00	127	75	12'6"	1.69
T352AA500X12.6	5	127	5.55	141	75	12'6"	2.16



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.