



T600AA Series

Hard Wall Marine Exhaust Hose USCG/SAE J1527 A2/B2

GENERAL APPLICATIONS

- Fuel, oil and hydraulic fluids suction and discharge
- Offers maximum flexibility
- Suitable for exhaust gas from water cooled stationary or marine diesel engines

CONSTRUCTION

Tube – Black NBR – exhaust gas, fuel and fire resistant

Reinforcement – High tensile textile cords with flexible steel helix wire – 4 ply

Cover – Black NBR/PVC blend – abrasion, ozone, hydrocarbon and fire resistant

WORKING PRESSURE

Constant Pressure – 2 Bar (30 PSI)

Burst Pressure – 5:1

SERVICE TEMPERATURE RANGE

-4°F (-20°C) to +212°F (+100°C)

BRANDING

ALFAGOMMA – ITALY 600 MARINE EXHAUST/FUEL S & D – <SIZE> – USCG/SAE J1527 TYPE A2 (in red letters)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T600AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T600AA062	5/8	16	1.02	26	30	30	2	25/50	0.36
T600AA075	3/4	19	1.14	29	30	30	2 1/4	25/50	0.44
T600AA087	7/8	22	1.26	32	30	30	2 3/4	25/50	0.50
T600AA100	1	25	1.38	35	30	30	3	25/50	0.56
T600AA112	1 1/8	28	1.50	38	30	30	3 1/4	25/50	0.60
T600AA125	1 1/4	32	1.65	42	30	30	3 3/4	25/50	0.65
T600AA137	1 3/8	35	1.77	45	30	30	4 1/4	25/50	0.70
T600AA150	1 1/2	38	1.89	48	30	30	4 1/2	25/50	0.76
T600AA162	1 5/8	42	2.17	52	30	30	5	25/50	0.81
T600AA175	1 3/4	45	2.16	55	30	30	5 1/4	25/50	0.87
T600AA189	1 7/8	48	2.28	58	30	30	5 3/4	25/50	0.91
T600AA200	2	51	2.40	61	30	30	6	25/50	0.99
T600AA225	2 1/4	57	2.64	67	30	30	6 3/4	25/50	1.09

* Does not meet J2006 or J1942 requirements.

See additional sizes...



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



T600AA Series

Hard Wall Marine Exhaust Hose USCG/SAE J1527 A2/B2

(continued from previous page)

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
T600AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T600AA238	2 3/8	60	2.76	70	30	27	7	25/50	1.25
T600AA250	2 1/2	63	2.87	73	30	27	7 1/2	25/50	1.31
T600AA275	2 3/4	70	3.11	80	30	27	8 1/4	25/50	1.41
T600AA300	3	76	3.39	86	30	27	9	25/50	1.53
T600AA350	3 1/2	90	3.94	100	30	27	10 1/2	25/50	1.91
T600AA400	4	102	4.41	112	30	27	12	25/50	2.12
T600AA450	4 1/2	115	5.00	127	30	27	13 1/2	25/50	2.72
T600AA500	5	127	5.55	141	30	24	15	25/50	3.04

* Does not meet J2006 or J1942 requirements.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.