



## T653AA Series

### Soft Wall Marine Exhaust Hose SAE J2006 R1

#### GENERAL APPLICATIONS

- Marine wet exhaust and bilge pump connections

**▲ Not for use with oils and fuels**

#### CONSTRUCTION

Tube – Black Synthetic Rubber.

Reinforcement – High tensile textile cords – 2 ply

Cover – Black Synthetic Rubber – abrasion, ozone and hydrocarbon resistant

#### WORKING PRESSURE

Constant Pressure – 5 Bar (75 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +212°F (+100°C)

#### BRANDING

ALFAGOMMA – ITALY – 653 SOFT WALL MARINE WET EXHAUST SAE J2006 R1 <SIZE> <YYYY MFG> (in blue letters)

View Up To Date Info



◀ SCAN OR VISIT  
**KOA.link/  
T653AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T653AA100	1	25	1.38	35	75	12.6	0.43
T653AA112	1 1/8	28	1.50	38	75	12.6	0.47
T653AA125	1 1/4	32	1.65	42	75	12.6	0.52
T653AA137	1 3/8	35	1.77	45	75	12.6	0.56
T653AA150	1 1/2	38	1.89	48	75	12.6	0.61
T653AA162	1 5/8	42	2.05	52	75	12.6	0.66
T653AA175	1 3/4	45	2.17	55	75	12.6	0.70
T653AA189	1 7/8	48	2.28	58	75	12.6	0.75
T653AA200	2	51	2.48	63	75	12.6	0.97
T653AA225	2 1/4	57	2.72	69	75	12.6	1.07
T653AA238	2 3/8	60	2.91	74	75	12.6	1.31
T653AA250	2 1/2	63	3.03	77	75	12.6	1.37
T653AA300	3	76	3.54	90	75	12.6	1.64
T653AA350	3 1/2	90	4.09	104	75	12.6	1.95
T653AA400	4	102	4.57	116	75	12.6	2.18

See additional sizes...



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



## T653AA Series

Soft Wall Marine Exhaust Hose SAE J2006 R1

**⚠ Not for use with oils and fuels**

*(continued from previous page)*

View Up To Date Info



← SCAN OR VISIT  
**KOA.link/  
T653AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T653AA450	4 1/2	115	5.08	129	75	12.6	2.43
T653AA500	5	127	5.55	141	75	12.6	2.68
T653AA600	6	152	6.61	168	75	12.6	3.26
T653AA662	6 5/8	168	7.24	184	75	12.6	3.57
T653AA800	8	203	8.70	221	75	12.6	4.96



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.