



SPN

SPN Series (Zinc Plated Steel)

Male NPT x Hose Shank



SPRN

SPRN Series (Zinc Plated Steel)

Jump Size Male NPT x Hose Shank

FEATURES AND ADVANTAGES

- Versatile hose connectors designed to connect hose and pipes of the same thread size.
- Frequently used in low pressure suction and discharge applications, and can be connected to many different types of strainers and couplings.
- Multi-serrated barb design allows for secure hose grip when properly clamped or crimped.

MATERIAL SPECIFICATIONS

- Complies with ASTM A53 B welded pipe.

VIEW ONLINE



SCAN FOR INFO

or visit

KOA.link/SPN-SPRN

Part Number	Thread Size NPT (in)	Hose Shank Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
SPN050	1/2	1/2	125	0.14	25
SPN075	3/4	3/4	125	0.22	25
SPRN-075100	1	3/4	125	0.35	100
SPN100	1	1	125	0.32	50
SPRN-100075	3/4	1	125	0.19	200
SPRN-100125	1 1/4	1	125	0.44	80
SPN125	1 1/4	1 1/4	125	0.56	20
SPRN-125100	1	1 1/4	125	0.30	80
SPRN-125150	1 1/2	1 1/4	125	0.65	60
SPN150	1 1/2	1 1/2	125	0.72	10
SPRN-150125	1 1/4	1 1/2	125	0.44	80
SPRN-150200	2	1 1/2	75	0.88	50
SPN200	2	2	75	1.10	40
SPRN-200150	1 1/2	2	75	0.73	60
SPRN-200250	2 1/2	2	75	1.65	20
SPN250	2 1/2	2 1/2	75	1.74	20
SPRN-250200	2	2 1/2	75	1.40	20
SPRN-250300	3	2 1/2	75	1.92	20
SPN300	3	3	75	2.18	12
SPRN-300250	2 1/2	3	75	1.91	20
SPRN-300400	4	3	75	2.95	8
SPN400	4	4	75	3.22	8
SPRN-400300	3	4	75	2.91	15
SPN600	6	6	75	12.24	4
SPN800	8	8	50	16.44	2
SPN1000	10	10	50	21.78	1
SPN1200	12	12	50	33.18	1

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.