



AB Series

Aluminum Shank with Brass Swivel Nut *(Complete Set)*

ABF Series

Aluminum Shank with Female Brass Swivel Nut

ABM Series

Aluminum Shank with Male Threads

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/AB

FEATURES AND ADVANTAGES

- Versatile threaded hose connectors designed for suction and discharge applications.
- Male ends supplied with NPSM threads (National Pipe Straight Mechanical).
- Cylindrical studs or “pins” positioned on the outside rim of the coupling allowing the use of a spanner wrench to tighten the coupling.

MATERIAL SPECIFICATIONS

- ASTM B85 Grade 383 aluminum alloy. (2 1/2", 6" sizes)
- ASTM B108-92 356 aluminum alloy. (1 1/2", 2", 3", 4" sizes)
- ASTM B283 Grade 37700 brass alloy. (1 1/2", 2", 3", 4" sizes)
- ASTM B584 Grade C85700 brass alloy. (4", 6" sizes)

Part Number	Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
AB150	1 1/2	75	0.56	75
AB200	2	75	0.88	40
AB250	2 1/2	50	1.34	18
AB300	3	50	2.70	12
AB400	4	50	4.42	10
AB600	6	25	8.30	4
<hr/>				
ABF150	1 1/2	75	0.38	150
ABF200	2	75	0.62	80
ABF250	2 1/2	50	0.94	36
ABF300	3	50	1.66	24
ABF400	4	50	2.72	20
ABF600	6	25	5.26	8
<hr/>				
ABM150	1 1/2	75	0.18	150
ABM200	2	75	0.25	80
ABM250	2 1/2	50	0.40	36
ABM300	3	50	1.04	24
ABM400	4	50	1.70	20
ABM600	6	25	3.04	8

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.