



Hammer Unions
HUT100 Series
Low Pressure Threaded Union
HUT200 Series
Low Pressure Threaded Union
HUT206 Series
Low Pressure Threaded Union

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/HUT-Low

FEATURES AND ADVANTAGES

- Applications include oil, gas, air, and water.
- Color-coded for easy identification.
- Unions are interchangeable with like products.
- CWP (Cold Working Pressure) is the maximum pressure at +70°F (+21°C).
- Figure 206 supplied with a Buna-N “O” Ring, which functions a secondary seal.

MATERIAL SPECIFICATIONS – BODY

- A-105/AISI 1020.

MATERIAL SPECIFICATIONS – NUT

- A-105/AISI 1020.

Part Number	Size (in)	CWP Rating at 70°F	Weight Each (lbs)	Standard Carton
HUT100-2	2	1000	5.29	6
HUT100-3	3	1000	11.60	5
HUT100-4	4	1000	17.75	3
HUT100-6	6	1000	44.40	1
HUT100-8	8	1000	69.90	1
HUT200-1	1	2000	1.55	30
HUT200-2	2	2000	4.55	12
HUT200-3	3	2000	11.70	5
HUT200-4	4	2000	19.00	3
HUT200-6	6	2000	44.40	1
HUT200-8	8	2000	71.45	1
HUT206-2	2	2000	4.60	12
HUT206-3	3	2000	11.80	5
HUT206-4	4	2000	19.10	3
HUT206-6	6	2000	45.00	1
HUT206-8	8	2000	66.00	1

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.