



Hammer Unions

HUT400 Series

Medium Pressure Threaded Union

HUT602 Series

Medium Pressure Threaded Union

VIEW ONLINE



SCAN FOR INFO
or visit

KOA.link/HUT-Med

FEATURES AND ADVANTAGES

- Applications include oil, gas, air, and water.
- Color-coded for easy identification.
- Unions are interchangeable with like products.
- CWP (Cold Working Pressure) is the maximum pressure at +70°F (+21°C).
- Figure 602 supplied with specially designed Buna-N lip type elastomer seal, which protects metal-to-metal sealing surfaces and reduces line flow turbulence.

MATERIAL SPECIFICATIONS – BODY

- AISI 1040.

MATERIAL SPECIFICATIONS – NUT

- AISI 1040.

Part Number	Size (in)	CWP Rating at 70°F	Weight Each (lbs)	Standard Carton
HUT400-2	2	4000	11.00	4
HUT400-3	3	4000	19.60	2
HUT400-4	4	4000	29.65	1
HUT602-1	1	6000	3.75	4
HUT602-2	2	6000	12.90	4
HUT602-3	3	6000	22.80	2
HUT602-4	4	6000	37.04	1

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.