



TCDA Series (Aluminum Part D x A)

API Female Coupler X Male Coupler

TCDD Series (Aluminum Part D x D)

API Female Coupler X Female Coupler

TCDC Series (Aluminum Part DC)

API Dust Cap

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/TCDA

GENERAL APPLICATIONS

Kuriyama Camlock Couplings are intended for use in many industrial applications. To learn more, please refer to pages 296-297 in this catalog.

FEATURES AND ADVANTAGES

- High quality design made for use in petroleum markets with bottom loading applications.
- API coupler end designed at a 22° angle for easy connecting and unrestricted off-loading.
- Aluminum alloy specially designed for high tensile strength and impact resistance.
- Supplied with forged brass handles, which results in less wear on connecting parts.

MATERIAL SPECIFICATIONS

- ASTM aluminum alloy.
- Supplied with a heavy-duty attachment chain.
- Zinc-plated carbon steel handle pins, pull rings and safety clips.
- Buna-N gasket included.

Part Number	API Size (in)	Coupler Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
TCDA-A4030	4	3	150	B26 Grade 713	4.25	4
TCDA-A4040	4	4	150	B26 Grade 713	4.50	4

Part Number	Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
TCDD-A4040	4	150	B26 Grade 713	6.00	2

Part Number	Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
TCDC-A400	4	150	B26 Grade 713	3.00	6

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.