



KLOC-SS-B

KLOC-SS-B Series

(316 Stainless Part B)

Female Coupler X Male NPT

KLOC-SS-D Series

(316 Stainless Part D)

Female Coupler X Female NPT



KLOC-SS-D

VIEW ONLINE



SCAN FOR INFO

or visit

KOA.link/KLOC2

GENERAL APPLICATIONS

Kuriyama Camlock Couplings are intended for use in many industrial applications. To learn more, please refer to pages 296-297 in this catalog.

FEATURES AND ADVANTAGES

- High quality design made for use in petroleum markets with bottom loading applications.
- Stainless steel alloy is analyzed on every melt, and specifically designed for high tensile strength and rigidity.
- Self-Locking handle provides maximum security and safety when connecting with male parts.

MATERIAL SPECIFICATIONS

- ASTM stainless steel alloy, specially designed for high tensile strength and impact resistance.
- Complies with Mil-Spec A-A-59326 for interchangeability.
- 304 stainless steel handles, handle pins, pull rings, and safety clips.
- Buna-N gasket included.

Part Number	Coupler Size (in)	NPT Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
KLOC-SS-B150	1 1/2	1 1/2	250	A666/316	1.57	20
KLOC-SS-B200	2	2	250	A666/316	2.00	16
KLOC-SS-B300	3	3	150	A666/316	3.63	4

Part Number	Coupler Size (in)	NPT Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
KLOC-SS-D150	1 1/2	1 1/2	250	A666/316	1.74	20
KLOC-SS-D200	2	2	250	A666/316	2.26	16
KLOC-SS-D300	3	3	150	A666/316	3.85	4

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.