



SDBC Series (Zinc Plated Carbon Steel)

Counterclockwise Spiral Double Bolt Clamp

SDBC-SS Series (304 Stainless Steel)

Counterclockwise Spiral Double Bolt Clamp

FEATURES AND ADVANTAGES

- Designed for use with hoses that have a convoluted cover or helix.
- Spiral design allows for premium sealing between the convolutions or helix.
- Hex nut for easy installation and cap nut to prevent injury from sharp bolt edges.
- SDBC and SDBC-SS series have a counterclockwise left hand spiral design.

MATERIAL SPECIFICATIONS

- 304 stainless steel spiral rod, saddle, washer, hex nut, cap nut.

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/SDBC

Part Number	Size (in)	Maximum Torque (ft lbs)	Weight Each (lbs)	Standard Carton
SDBC-1.5	1 1/2	6	0.18	100
SDBC-2	2	6	0.36	100
SDBC-2.25	2 1/4	6	0.40	100
SDBC-2.5	2 1/2	8	0.48	100
SDBC-3	3	8	0.66	70
SDBC-3.5	3 1/2	8	0.70	70
SDBC-4	4	24	1.02	40
SDBC-5	5	24	1.76	30
SDBC-6	6	30	2.00	20
SDBC-8	8	30	2.76	10
SDBC-10	10	30	3.46	10
SDBC-12	12	30	4.14	10
SDBC-SS-1.5	1 1/2	6	0.20	100
SDBC-SS-2	2	6	0.40	100
SDBC-SS-2.5	2 1/2	6	0.55	100
SDBC-SS-3	3	8	0.73	70
SDBC-SS-3.5	3 1/2	8	0.94	100
SDBC-SS-4	4	24	1.12	40
SDBC-SS-5	5	24	1.94	30
SDBC-SS-6	6	30	2.20	20
SDBC-SS-8	8	30	3.04	10
SDBC-SS-10	10	30	3.81	10
SDBC-SS-12	12	30	4.55	10

NOTES:

- Two or more Spiral Bolt Clamps are suggested for 3" ID and larger hoses.
- Both hex nuts should be tightened equally to prevent leakage.
- Suggested SDBC/SDBC-SS sizes to use with Tigerflex Metric sized hoses: WT, WE 45M 1.77" ID – Suggested SDBC-2 and SDBC-SS-2 WT, WE 57M 2.24" ID – Suggested SDBC-2.25 WT, WE 60M 2.36" ID – Suggested SDBC-2.5 and SDBC-SS-2.5

CAUTION:

- Proper evaluation of holding power for each clamp must be determined for each individual application.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.