



KuriCrimp[™] Ferrules

Features and Material Specifications

Plated Steel Crimp Ferrules

FEATURES AND ADVANTAGES

- Ferrules designed for use with fittings that have interlocking collars.
- Zinc plated steel.

MATERIAL SPECIFICATIONS

• AISI 1008.

Stainless Steel Crimp Ferrules

FEATURES AND ADVANTAGES

- Ferrules designed for use with fittings that have interlocking collars.
- 304 stainless steel.

MATERIAL SPECIFICATIONS

ASTM A666 304 SS.

KuriCrimp™ Ferrules are designed for use with the following Kuriyama fitting and coupling items.

| Aluminum | | |
|--------------|-------------------------------|--|
| Series | Size (in) | |
| AL-C | 1 1/2 · 2 · 2 1/2 · 3 · 4 · 6 | |
| AL-E | 1 1/2 · 2 · 2 1/2 · 3 · 4 · 6 | |
| ALSH-C | 1 1/2 · 2 · 2 1/2 · 3 · 4 | |
| Brass | | |
| Series | Size (in) | |
| BR-C | 1 1/2 · 2 · 3 · 4 | |
| BR-E | 1 1/2 · 2 · 3 · 4 | |
| Ductile Iron | | |
| Series | Size (in) | |
| DI-C | 4 | |
| DI-E | 4 | |
| | | |

| Stainless | |
|-----------|-----------------------------------|
| Series | Size (in) |
| CRN-SS | 1 · 1 1/2 · 2 · 2 1/2 · 3 · 4 |
| FB-SS | 1 · 1 1/2 · 2 · 2 1/2 · 3 · 4 |
| FILS-SS | 1 1/2 · 2 · 3 · 4 |
| MBS-SS | 1 · 1 1/2 · 2 · 2 1/2 · 3 · 4 |
| MILS-SS | 1 1/2 · 2 · 3 · 4 |
| SS-C | 1 1/2 · 2 · 3 · 4 |
| SS304-C | 1 1/2 · 2 · 3 · 4 |
| TCS-SS | 1 · 1 1/2 · 2 · 2 1/2 · 3 · 4 |
| TES-SS | 3 · 4 |
| Steel | |
| Series | Size (in) |
| CRN | 1 · 1 1/2 · 2 · 2 1/2 · 3 · 4 · 6 |
| TBN | 1 1/2 · 2 · 2 1/2 · 3 · 4 · 6 |
| | |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

