



## Sandblast Couplings & Accessories

### Two Lug Hose Couplings

**Q-AL Series (Aluminum)**

**Q-BR Series (Brass)**

**Q-PI Series (Plated iron)**

**VIEW ONLINE**



SCAN FOR INFO  
or visit  
[KOA.link/Q-X](https://KOA.link/Q-X)

#### FEATURES AND ADVANTAGES

- Couplings designed specifically for sandblast hoses.
- Two claw couple design for quick connection.
- Available in aluminum, brass and plated iron.
- Available in both standard and full flow design. Full flow design removes air restrictions present in the standard design, and increases PSI available to the nozzle.
- Sheet metal screws supplied with each.

#### MATERIAL SPECIFICATIONS

- Aluminum – ASTM B26, Grade 713.
- Brass – ASTM B584, Grade C85700.
- Ductile Iron Plated – ASTM A536, Grade 65/45/12.

Part Number	Hose ID (in)	Hose OD (in)	PSI Rating at 70°F	Gasket	Flow Size	Weight Each (lbs)	Standard Carton
Q-AL050	1/2	1 1/16	150	SBG	STD	0.15	6
Q-AL1	3/4	1 1/2	150	SBG	STD	0.36	6
Q-AL2	1	1 7/8	150	SBG	STD	0.36	6
Q-AL3	1 1/4	2 5/32	150	SBG	STD	0.66	6
Q-AL4	1 1/2	2 3/8	150	SRG-2	STD	0.88	6
Q-AL5	1 1/2	2 3/8	150	SRG-2	FULL	1.10	6
Q-AL6	2	2 7/8	150	SRG-2	FULL	1.45	6
Q-BR1	3/4	1 1/2	175	SBG	STD	1.06	6
Q-BR2	1	1 7/8	175	SBG	STD	1.12	6
Q-BR3	1 1/4	2 5/32	175	SBG	STD	1.94	6
Q-BR4	1 1/2	2 3/8	175	SRG-2	STD	2.64	6
Q-BR5	1 1/2	2 3/8	175	SRG-2	FULL	3.50	6
Q-BR6	2	2 7/8	175	SRG-2	FULL	4.75	6
Q-PI1	3/4	1 1/2	175	SBG	STD	0.98	10
Q-PI2	1	1 7/8	175	SBG	STD	1.02	10
Q-PI3	1 1/4	2 5/32	175	SBG	STD	1.84	10
Q-PI4	1 1/2	2 3/8	175	SRG-2	STD	2.38	10

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.