





— VIEW ONLINE



SCAN FOR INFO

or visit

KOA.link/PPD

PPD Series (Polypropylene Part D)

Female Coupler X Female NPT

GENERAL APPLICATIONS

Kuriyama Camlock Couplings are intended for use in many industrial applications. To learn more, please refer to pages 296-297 in this catalog.

FEATURES AND ADVANTAGES

- Polypropylene material is glass filled for added strength and durability.
- Extremely lightweight yet strong.
- Precision molded to ensure consistency in form and function.
- Economical when compared with other materials.

MATERIAL SPECIFICATIONS

- Glass filled Polypropylene.
- Complies with Mil-Spec A-A-59326 for interchangeability in relevant sizes.
- Locking feature using safety clips to prevent disconnection during use.
- Supplied 304 stainless steel handles, handle pins, pull rings, and safety clips.
- All 4" size female couplers supplied with three handles to provide added stability.
- EPDM gasket included.

| Part Number | Size (in) | PSI Rating at 70°F | Weight Each (lbs) | Standard Carton |
|-------------|--------------|-----------------------|----------------------|-----------------|
| PPD050 | 1/2 | 100 | 0.18 | 100 |
| PPD075 | 3/4 | 100 | 0.19 | 50 |
| PPD100 | 1 | 100 | 0.25 | 30 |
| PPD125 | 1 1/4 | 100 | 0.41 | 40 |
| PPD150 | 1 1/2 | 100 | 0.53 | 30 |
| PPD200 | 2 | 100 | 0.55 | 40 |
| PPD300 | 3 | 50 | 1.17 | 20 |
| PPD400 | 4 | 50 | 1.58 | 10 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

