Kuriyama-Couplings

Valves



Polypropylene Ball Valve 4-Bolt Design

· · · · ·				
Part Number	Size (in.)	Weight Each (lbs.)	Standard Carton	
PPBV050	1/2	0.88	24	
PPBV075	3/4	0.85	24	
PPBV100	1	1.16	24	
PPBV125	1 1/4	1.65	24	
PPBV150	1 1/2	1.67	24	

Polypropylene Ball Valve 6-Bolt Design

Part Number	Size (in.)	Weight Each (lbs.)	Standard Carton
PPBV200	2	3.71	8
PPBV300	3	6.60	6
PPBV400	4	9.90	2

150 PSI

100 PSI

PSI Rating @ 70°F (+21°C)

PPBV Specifications

1/2" - 1 1/2"

2" - 4"

Features & Benefits

- Full port
- Stainless steel bolts and nuts
- Teflon[™] seals
- Viton[®] O-Ring stems and seals
- Polypropylene material is glass filled for extra strength
- Female NPT threads

Viton[®] is a registered trademark of DuPont Performance Elastomers. Teflon[™] is a registered trademark of The Chemours Company FC, LLC.



Foot Valve

Size (in.)	Weight Each (lbs.)	Standard Carton			
1 1/2	2.90	12			
2	5.30	8			
2 1/2	7.30	6			
3	9.00	5			
4	17.90	2			
6	46.60	1			
8	93.70	1			
	(in.) 1 1/2 2 2 1/2 3 4 6	(in.) (lbs.) 1 1/2 2.90 2 5.30 2 1/2 7.30 3 9.00 4 17.90 6 46.60			

Kuriyama foot valves are made of cast iron and come with a neoprene flapper valve assembly. Threads are NPT; bolts and nuts are plated steel. Designed for use in irrigation and other pumping applications where water may be dirty due to silt and sand to prevent passage of contaminants to the pump.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

장 Kuriyama of America, Inc.