

T959 - AUTOLOCK EVOLUTION EPDM



Liquid cooling 16 bar (240 psi) - EPDM
UL 94 V0

Tube: Black peroxide cured EPDM, Calcium and Zinc free.
Reinforcement: High tensile textile braids.

Cover: black/red/blue EPDM - abrasion, ozone and UL94 V0 flame resistant.
ID≤1" smooth finish, ID≥1 1/4" wrapped.

Application: Data center liquid cooling. Compatible with push-on fittings.
Temperature: -40 °C +120 °C (-40 °F +248 °F)

Series Number	Color	ID		OD		Max. Working Pressure (psi)	Burst Pressure (psi)	Bend Radius		Weight lbs/ft	Approx. Length (ft)
		(in)	(mm)	(in)	(mm)			(in)	(mm)		
T959AA019*	Black	3/16	5	0.43	11	240	960	0.79	20	0.07	800
T959AA025*	Black	1/4	6	0.51	13	240	960	0.94	24	0.1	600
T959AA038*	Black	3/8	10	0.67	17	240	960	1.57	40	0.17	600
T959AA050*	Black	1/2	13	0.87	22	240	960	2.05	52	0.22	550
T959AA062*	Black	5/8	16	0.98	25	240	960	2.52	64	0.27	350
T959AA075*	Black	3/4	19	1.14	29	240	960	2.99	76	0.34	350
T959AA100*	Black	1	25	1.42	36	240	960	3.94	100	0.47	200
T959AA125X200^	Black	1 1/4	32	1.77	45	240	960	5.04	128	0.69	200
T959AA150X200^	Black	1 1/2	38	2.01	51	240	960	5.98	152	0.8	200
T959AA200X200^	Black	2	51	2.56	65	240	960	8.03	204	1.13	200
T959AH019*	Red	3/16	5	0.43	11	240	960	0.79	20	0.07	800
T959AH025*	Red	1/4	6	0.51	13	240	960	0.94	24	0.1	600
T959AH038*	Red	3/8	10	0.67	17	240	960	1.57	40	0.17	600
T959AH050*	Red	1/2	13	0.87	22	240	960	2.05	52	0.22	550
T959AH062*	Red	5/8	16	0.98	25	240	960	2.52	64	0.27	350
T959AH075*	Red	3/4	19	1.14	29	240	960	2.99	76	0.34	350
T959AH100*	Red	1	25	1.42	36	240	960	3.94	100	0.47	200
T959AH125X200^	Red	1 1/4	32	1.77	45	240	960	5.04	128	0.69	200
T959AH150X200^	Red	1 1/2	38	2.01	51	240	960	5.98	152	0.8	200
T959AH200X200^	Red	2	51	2.56	65	240	960	8.03	204	1.13	200
T959AE019*	Blue	3/16	5	0.43	11	240	960	0.79	20	0.07	800
T959AE025*	Blue	1/4	6	0.51	13	240	960	0.94	24	0.1	600
T959AE038*	Blue	3/8	10	0.67	17	240	960	1.57	40	0.17	600
T959AE050*	Blue	1/2	13	0.87	22	240	960	2.05	52	0.22	550
T959AE062*	Blue	5/8	16	0.98	25	240	960	2.52	64	0.27	350
T959AE075*	Blue	3/4	19	1.14	29	240	960	2.99	76	0.34	350
T959AE100*	Blue	1	25	1.42	36	240	960	3.94	100	0.47	200
T959AE125X200^	Blue	1 1/4	32	1.77	45	240	960	5.04	128	0.69	200
T959AE150X200^	Blue	1 1/2	38	2.01	51	240	960	5.98	152	0.8	200
T959AE200X200^	Blue	2	51	2.56	65	240	960	8.03	204	1.13	200

Packing:

* Reel max 3 pcs, min 50ft with reel.
^ 200' fixed no reel - coiled

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.