



Redi-MaxTM

REDIMAX Series

Non-Conductive High Oil-Resistant General Service Hose

GENERAL APPLICATIONS

- Diesel
 - Fuel oil
 - Oil
 - Other petroleum products

⚠ Do not use this product for curb pump fueling applications

⚠ Not recommended for unleaded gasoline

CONSTRUCTION

Tube – Black NBR, ARPM Class A High Oil Resistant

Reinforcement – Spiral polyester yarn

Cover – Red NBR, ARPM Class A High Oil Resistant

SERVICE TEMPERATURE RANGE

-20°F (-29°C) to +180°F (+82°C)

BRANDING

REDI-MAX HIGH OIL RESIST. NON-CONDUCTIVE-SIZE-WP-MADE IN USA

FEATURES AND ADVANTAGES

- Long lengths on reels.
 - Non-Conductive - tested to exceed minimum electrical resistance greater than one (1) MEGOHM per inch of hose length at 1000 volts DC.

View Up To Date Info



◀ SCAN OR VISIT

KOA.link/REDIMAX

PACKAGING

Maximum 2 pcs. on reel

SAFETY FACTOR

4:1

Part Number		Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
REDIMAX-025x700		Red	1/4	0.62	300	700	112
REDIMAX-038x700		Red	3/8	0.69	300	700	126
REDIMAX-050x700		Red	1/2	0.84	300	700	175
REDIMAX-075x700		Red	3/4	1.15	300	700	294
REDIMAX-100x700		Red	1	1.43	300	700	441
REDIMAX-125x500		Red	1 1/4	1.78	250	500	405
REDIMAX-150x400		Red	1 1/2	2.03	250	400	380

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.