TECHNICAL

ALFACOMMA.

ABT5K - Alfabiotech 5000 MINETUFF

Alfabiotech 5000 MINETUFF - ABT5K Hydraulic Hose

ABT5K - 4 or 6 wire spiral

Exceeds EN856 4SP sizes 5/8", 3/4" and 1"

Exceeds EN856 4SH sizes 1 1/4" Exceeds SAE 100R13 sizes 5/8" through 2"

ISO 18752/CC 1,000,000+ impulse cycles all sizes

MSHA IC-152/16 approved flame resistance







General Applications:

Developed to withstand very demanding conditions very high performance in pressure, pulsing and flexing.

Construction:

Tube – Oil resistant synthetic rubber and biodegradable hydraulic fluids.

Reinforcement – Four/six high tensile steel spirals.

Cover – Abrasion, ozone and hydrocarbon resistant synthetic rubber.

Service Temperature Range:

-40°F (-40°C) to +250°F (+121°C)

Branding:

ALFAGOMMA ALFABIOTECH 5K MINETUFF ... WP 35 MPa (5000 PSI) - ISO 18752/CC - MSHA IC-152/16 - MADE IN ITALY

Length:

Random up to 1" - 200 feet from 1 1/4" to 1 1/2" - 100 feet from 2" to 2 1/2"

Nomi	Nominal Specifications													
Series Number	Size Code	ID		OD		Max	Min. Bend. Radius			Coupling Recommendations				
			(mm)	(in)	(mm)	Working [†] Pressure (psi)	(in)	(mm)	Weight (lbs/ft)	AlfaCrimp		Two-Piece Ferrule Ferrule		
										One-l	Piece	Skive	Interlock	
ABT5K	10	5/8	15.9	1.04	26.3	5000	5.5	139.7	0.63			AS4		
ABT5K	12	3/4	19.1	1.22	31.0	5000	5.9	149.9	0.83		F	AS4	XF2	
ABT5K	16	1	25.4	1.48	37.6	5000	7.0	177.8	1.13	D	F	AS4	XF2	
ABT5K	20	1 1/4	31.8	1.80	45.8	5000	11.0	279.4	1.70		F		XF2	
ABT5K	24	1 1/2	38.1	2.22	56.5	5000	19.6	497.8	3.02		F		XF1	
ABT5K	32	2	50.8	2.76	70.2	5000	21.6	548.6	4.14		F		XF1	
ABT5K	40	2 1/2	63.5	3.26	82.8	5000	32.3	820.4	5.08				XF1	

[†] Minimum burst pressure 4-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.