

KK4PW - K-Kleen Assemblies



HOSES
ONE-PIECE B SERIES
ONE-PIECE D SERIES
ONE-PIECE F & P SERIES
TWO-PIECE FERRULES (A & PFR SERIES)
TWO-PIECE INSERTS (A SERIES)
TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)
QUICK RELEASE
ASSEMBLY EQUIPMENT

K-Kleen™

Pressure Washer Hose Assemblies

KK4PW™ Series

General Applications:

High pressure cleaning hose. For heavy duty use with hot and cold water and detergent fluids, and high pressure cleaning equipment. Extremely flexible, light weight and easy to handle. Use bend restrictors to extend service life. Not recommended for steam or steam cleaner service.

BK = Black Cover

BU = Blue Cover (non-marking)

Construction:

Tube – Synthetic rubber, black... hot water-resistant.

Reinforcement – High tensile steel wire braid.

Cover – Pin-pricked, synthetic rubber, black or blue (non-marking), weather, oil and abrasion resistant.

Ends – Rigid male NPT x swivel male NPT ends with bend restrictors on each end.



KK4PW-BK
Black color



KK4PW-BU
Blue color

Service Temperature Range:

-40°F (-40°C) to +300°F (+155°C) constant operation

Maximum operating temperature:
+300°F (+155°C)

Air maximum temperature: +175°F (+80°C)

Note: Operating temperatures in excess of +300°F (+155°C) may materially reduce the life of the hose.

Branding:

ALFAGOMMA K-KLEEN 4000 PSI ID ...DN ... 280 Bar WP - 155°C

Nominal Specifications

Part Number	Hose ID (in)	Hose OD (in)	Color	Working Pressure (psi)	Min. Bending Radius (in)	Length (ft)	Weight (lbs/each)
KK4PW06BUMMSX50	3/8	0.61	Blue	4000	2.5	50	10.5
KK4PW06BKMSX50	3/8	0.61	Black	4000	2.5	50	10.5
KK4PW06BUMMSX100	3/8	0.61	Blue	4000	2.5	100	19.5
KK4PW06BKMSX100	3/8	0.61	Black	4000	2.5	100	19.5
KK4PW08BUMMSX50	1/2	0.76	Blue	4000	3.5	50	15.0
KK4PW08BKMSX50	1/2	0.76	Black	4000	3.5	50	15.0
KK4PW08BUMMSX100	1/2	0.76	Blue	4000	3.5	100	27.5
KK4PW08BKMSX100	1/2	0.76	Black	4000	3.5	100	27.5

(3:1) Safety Factor

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

TECHNICAL INFORMATION