

## Waterblast Hose WB 15



**NEW**

**WB15 –  
4 wire spiral**

### General Applications:

High pressure water jetting

### Construction:

**Tube** – Oil and water resistant synthetic rubber.

**Reinforcement** – Four high tensile steel spirals.

**Cover** – Oil, water and ozone resistant synthetic rubber.

### Service Temperature Range:

Constant operation: +14°F (-10°C) to +158°F (+70°C)

### Branding:

Dunlop Hiflex

### Length:

Random length coils, all in multiples of 50 feet.

Examples: 200', 250', 300', 350'

## Nominal Specifications

Series Number	Size Code	ID		OD		Max Working <sup>†</sup> Pressure (psi)	Min. Bend. Radius		Weight (lbs/ft)	Coupling Recommendations	
		(in)	(mm)	(in)	(mm)		(in)	(mm)		Two-Piece Ferrule Interlock	Ferrule Interlock
WB15	08	1/2	12.7	1.00	25.4	16000	8.0	203.2	0.75	WF9	
WB15	12	3/4	19.1	1.25	31.8	14500	11.0	279.4	1.13	WF9	

<sup>†</sup> Minimum burst pressure: 2.5:1 safety factor.

**Freight:** Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.