

Single wire braid light weight cleaning hose on easy-to-handle reels – KK4BK/BU



KK4BK (Black) – Single wire braid

NEW



KK4BU (Blue) – Single wire braid

General Applications:

High pressure cleaning hose. For heavy duty use with hot and cold water and detergent fluids, and high pressure cleaning equipment. Extremely flexible, light weight and easy to handle. Use bend restrictors to extend service life. Not recommended for steam or steam cleaner service.

BK = Black Cover

BU = Blue Cover (non-marking)

Construction:

Tube – Synthetic rubber, black... hot water-resistant.

Reinforcement – High tensile steel wire braid.

Cover – Pin-pricked, black synthetic rubber, weather, oil, ozone, and abrasion resistant. Blue cover version is non-marking.

Service Temperature Range:

-40°F (-40°C) to +300°F (+155°C) constant operation.

Maximum operating temperature:

+300°F (+155°C)

Air maximum temperature: +175°F (+80°C)

Note: Operating temperatures in excess of +300°F (+155°C) may materially reduce the life of the hose.

Branding:

ALFAGOMMA K-KLEEN 4000 PSI ID ...DN ... 280 Bar WP - 155°C

Nominal Specifications

Series Number	Size Code	ID		OD		Max Working Pressure (psi)	Min. Bend. Radius		Weight (lbs/ft)	Coupling Recommendations		
		(in)	(mm)	(in)	(mm)		(in)	(mm)		AlfaCrimp One-Piece	Two-Piece Ferrule Non-Skive	
KK4BK	06	3/8	9.5	0.61	15.4	4000	2.5	63.5	0.18	B		AF1
KK4BK	08	1/2	12.7	0.76	19.2	4000	3.5	88.9	0.25	B		AF1
KK4BU	06	3/8	9.5	0.61	15.4	4000	2.5	63.5	0.18	B		AF1
KK4BU	08	1/2	12.7	0.76	19.2	4000	3.5	88.9	0.25	B		AF1

Minimum burst pressure 3-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Bend Restrictors available for K-KLEEN 4000 hoses, refer to the following part numbers:



RBR-19x150 for use on KK4BK/BU-06

RBR-22x150 for use on KK4BK/BU-08

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

- HOSES
- ONE-PIECE B SERIES
- ONE-PIECE D SERIES
- ONE-PIECE F & P SERIES
- TWO-PIECE FERRULES (A & PFR SERIES)
- TWO-PIECE INSERTS (A SERIES)
- TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)
- QUICK RELEASE
- ASSEMBLY EQUIPMENT
- TECHNICAL INFORMATION