

General Applications:

Forest Lite[™] Type 2 is a single jacket, polyurethane lined lightweight hose intended for use in wildland fire suppression

Construction:

Lining – The Thermoplastic extruded PU interior lining shall be a single-ply extruded tube and shall be unaffected by ozone. The finished form shall be free of pits or other imperfections and shall have a smooth finish. No reclaimed material shall be used.

Jacket Construction – The jacket is a combination of 100% virgin synthetic high tenacity virgin synthetic yarn and spun yarn. The jacket is thoroughly impregnated with a polymer compound, yellow in color, to provide superior resistance to chemicals, abrasion and ultra-violet light. Hose shall be firm in texture, flexible and free from knots, lumps and irregularities. The jacket shall be treated to be resistant to mildew.

Color - Yellow

Service Temperature Range:

-40°F to +150°F (-40°C to +65°C)

Features and Advantages:

- Meets or exceeds National Fire Products Association (NFPA) 1961 Standard on Fire Hose (current edition) as well as U.S. Forest Service F-187 standard.
- ISO 9001 Forest Lite[™] Type 2 fire hose products are manufactured in a registered facility in Buenos Aires, Argentina.

Couplings:

Expansion-type hard coat anodized aluminum. NST, NPSH, or Quarter-Turn couplings are available.

Packaging:

Available in 50' and 100' lengths. Ease of Packing – Lightweight, extremely flexible and easy to pack.

| Nominal Specifications | | | | | | | | | |
|------------------------|--------------|--------|--------------------------|------------------|--------------------------|------------------------|------------------------|------------------------------|---------------------------------|
| Part Number* | Size (in) | Color | Coupling Size (in) | Coupling Type | Service Test (psi) | Proof Test (psi) | Burst Test (psi) | Available Lengths (ft) | Weight Uncoupled (lbs/ft) |
| F2100YXXX-NH100 | 1 | Yellow | 1 | NST | 300 | 600 | 900 | 50/100 | 0.08 |
| F2100YXXX-NP100 | 1 | Yellow | 1 | NPSH | 300 | 600 | 900 | 50/100 | 0.08 |
| F2100YXXX-QT100 | 1 | Yellow | 1 | 1/4 TURN | 300 | 600 | 900 | 50/100 | 0.08 |
| F2150YXXX-NH150 | 1 1/2 | Yellow | 1 1/2 | NST | 300 | 600 | 900 | 50/100 | 0.14 |
| F2150YXXX-NP150 | 1 1/2 | Yellow | 1 1/2 | NPSH | 300 | 600 | 900 | 50/100 | 0.14 |
| F2150YXXX-QT150 | 1 1/2 | Yellow | 1 1/2 | 1/4 TURN | 300 | 600 | 900 | 50/100 | 0.14 |

*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS. WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.