



NEW
ITEMS

King Bee™

KBEE™ Series

Polyethylene Hose Guard



General Applications:

- Protection of high pressure sewer jetting hoses

Construction: Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends.

Service Temperature: -40°F (-40°C) to 150°F (+65°C)*

Features and Advantages:

- **Easy Slide Interior** – low coefficient of friction polyethylene tube allows for sewer jetting hoses to slide through easily, protecting them from wear.
- **“Cold-Flex” Materials** – Remains flexible in sub-zero temperatures.
- **Crush Resistant** – Will spring back to original shape after being crushed, will not kink!
- **Easy Slide Helix** – Exposed ribs protect tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.
- **Leak Proof Cuffs** – Overmolded cuffs will not separate from the hose guard. Each cuff and unit is 100% factory tested.



King Bee™ Collar Clamp with 20' Rope

- Corrosion resistant stainless steel
- Adjustable sizing

Part Number	ID (in.)	Weight (lbs.)
KBC300	3	0.67



(Hose sold separately)

Nominal Specifications

Part Number	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Working Pressure (psi @ 68°F)	Vacuum Rating (in. Hg @ 68°F)	Min. Bending Radius (in. @ 68°F)	Standard Length (ft.)	Weight per Pkg. (lbs.)
KBEE2X3	2	50.8	2.76	70.1	15	29	3.5	3	2.55
KBEE3X3	3	76.2	4.06	103.1	7	29	6.5	3	4.80

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

*Actual service temperature range is application dependent.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

KKBBR0217