



K2163 Series

Contractor PVC Water Hose

GENERAL APPLICATIONS

- Construction water transfer
- Heavy duty industrial and commercial watering
- Irrigation supply lines
- Municipal maintenance watering

CONSTRUCTION

- Tube – Black phthalate free PVC
- Reinforcement – High tensile strength yarn
- Cover – Black phthalate free PVC

SERVICE TEMPERATURE RANGE

+25°F (-4°C) to +150°F (+65°C)

View Up To Date Info



◀ SCAN OR VISIT

[KOA.link/
K2163](https://koi.link/K2163)



MADE IN NORTH AMERICA

FEATURES AND ADVANTAGES

- **UV and Weather Resistant** – Opaque cover resists damage from UV light and weather aging.
 - **Abrasion Resistant PVC** – Durable PVC holds up better than rubber water hoses when dragged.
- **Lightweight** – Lighter weight than rubber hoses, reduces worker fatigue.
 - **Non-Marking Cover** – Can be dragged over flooring without leaving marks typical of rubber hoses.

Series Number	Size Code	ID		OD		Max. Working Pressure† (psi)		Standard Length (ft)	Weight per Pkg. (lbs)
		(in)	(mm)	(in)	(mm)	at 70°F (20°C)	at 122°F (50°C)		
K2163	12	3/4	19.1	1.030	26.2	150	75	300	65

NOTES:

† Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.