



HSC2960 Series

Reinforced Polyurethane Self-Store Coiled Hose Assembly

FEATURES AND ADVANTAGES

- **High Oil Resistance** – Meets ARPM Class A rating for high oil resistance. Remains flexible when exposed to oils. Won't dry out or crack like other PVC hoses.
- **Highly Abrasion Resistant** – Designed for applications where severe abrasion is a factor. Provides for longer hose life and lower operating costs versus rubber or PVC hoses.
- **Cold Flex Materials** – Remains flexible and easy to handle in sub-zero temperatures.
- **Lightweight** – Lighter weight to reduce worker fatigue.

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +185°F (+85°C)

Note: Each length of assembled hose includes a 4" pigtail and a 20" whip end, assembled to 1/4" or optional 3/8" (priced upon request) male NPT permanent crimped swivel brass fittings with rubber bend restrictors. Working length is 80% of nominal length shown.

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
HSC2960](https://KOA.link/HSC2960)

Series Number HSC2960 Aqua Tint	Size Code x Length	ID		OD		Max. Working Pressure [†] (psi)		Working Length (ft)	Coil OD (in)	Standard Package	Weight per Pkg. (lbs)
		(in)	(mm)	(in)	(mm)	at 70°F (20°C)	at 122°F (50°C)				
✓	04 x 15	1/4	6.5	0.395	9.5	225	125	12	2	10	6.5
✓	04 x 25	1/4	6.5	0.395	9.5	225	125	20	2	10	10.0
✓	04 x 50	1/4	6.5	0.395	9.5	225	125	40	2	1	2.0
✓	06 x 15	3/8	9.5	0.570	14.5	225	125	12	3	5	7.0
✓	06 x 25	3/8	9.5	0.570	14.5	225	125	20	3	5	11.0
✓	06 x 50	3/8	9.5	0.570	14.5	225	125	40	3	1	4.0

NOTES:

† Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.