



TUNDRA **HOSE**[™]

**HS1231 Series / HS1234 Series /
HS1236 Series**

Ultra-Flexible Low Temperature PVC Air Hose Assemblies

FEATURES AND ADVANTAGES

- **Extreme Cold Flex Materials** – Remains flexible and easy to handle in sub-zero temperatures to -65°F (-54°C).
- **Abrasion Resistant PVC** – Durable PVC holds up better than rubber air hoses when dragged.
- **Medium Oil Resistance** – Meets ARPM Class B rating for medium oil resistance. Remains flexible when exposed to oils. Won't dry out or crack like other PVC hoses.
- **Lightweight** – Lighter weight reduces worker fatigue.
- **Non-Marking Cover** – Can be dragged over flooring without leaving marks typical of rubber hoses.

SERVICE TEMPERATURE RANGE

-65°F (-54°C) to +150°F (+65°C)



View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
HS1231-4-6**



Series Number			Size Code	ID		OD		Max. Working Pressure [†] (psi)		Assembled Lengths (ft)	Weight per Pkg. (lbs)		
HS1231 Yellow	HS1234 Red	HS1236 Blue		(in)	(mm)	(in)	(mm)	at 70°F (20°C)	at 122°F (50°C)		25 (ft)	50 (ft)	100 (ft)
✓	✓	✓	04	1/4	6.5	0.500	12.7	300	160	25/50/100	2.0	4.0	7.8
✓	✓	✓	06	3/8	9.5	0.625	15.9	300	160	25/50/100	2.8	5.5	10.7
✓	✓	✓	08	1/2	12.7	0.781	19.8	300	160	25/50/100	4.1	8.1	16.0

NOTES:

- † Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.
- Hose assemblies are furnished with the following brass fittings: 1/4" ID – 1/4" X 1/4" M NPT, 3/8" ID – 3/8" X 1/4" M NPT, 1/2" ID – 1/2" X 3/8" MNPT.
 - Refer to page 49 for Technical Information.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.