



View Up To Date Info



◀ SCAN OR VISIT
KOA.link/HS1181-4-6



HS1181 Series / HS1184 Series / HS1186 Series

Utility Grade PVC Air Hose Assemblies

FEATURES AND ADVANTAGES

- **Economical** – Remains flexible and easy to handle in sub-zero temperatures.
- **Abrasion Resistant PVC** – Durable PVC holds up better than rubber air hoses when dragged.
- **Medium Oil Resistant** - Meets ARPM Class B rating for medium oil resistance. Remains flexible when exposed to oils. Won't dry out or crack like other PVC hoses.
- **Lightweight** – Lighter weight than rubber hoses, reduces worker fatigue.
- **Non-Marking Cover** – Can be dragged over flooring without leaving marks typical of rubber hoses.

SERVICE TEMPERATURE RANGE

+14°F (-10°C) to +150°F (+65°C)

Series Number			Size Code	ID		OD		Max. Working Pressure [†] (psi) at 70°F (20°C)	Assembled Lengths (ft)	Weight per Pkg. (lbs)		
HS1181 Yellow	HS1184 Red	HS1186 Blue		(in)	(mm)	(in)	(mm)			25 (ft)	50 (ft)	100 (ft)
✓	✓	✓	04	1/4	6.5	0.475	12.1	300	25/50/100	1.9	3.7	7.4
✓	✓	✓	06	3/8	9.5	0.600	15.2	300	25/50/100	2.6	5.1	10.2

NOTES:

- † Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.
- Hose assemblies are furnished with the following brass fittings: 1/4" ID – 1/4" X 1/4"M NPT, 3/8" ID – 3/8" X 1/4"M NPT.
 - Refer to page 53 for Technical Information.

COMPLIANCES (for details see page 91)

Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.