



TUNDRA **HOSE™**

HS1232W Series

Ultra-Flexible Low Temperature PVC Water Hose Assemblies

FEATURES AND ADVANTAGES

- **Extreme Cold Flex Materials** – Remains flexible and easy to handle in sub-zero temperatures to -65°F (-54°C).
- **Abrasion Resistant PVC** – Durable PVC holds up better than rubber air hoses when dragged.
- **Medium Oil Resistance** – Meets ARPM Class B rating for medium oil resistance. Remains flexible when exposed to oils. Won't dry out or crack like other PVC hoses.
- **Lightweight** – Lighter weight reduces worker fatigue.
- **Non-Marking Cover** – Can be dragged over flooring without leaving marks typical of rubber hoses.

SERVICE TEMPERATURE RANGE

-65°F (-54°C) to +150°F (+65°C)



View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
HS1232W**



Series Number	Size Code	ID		OD		Max. Working Pressure† (psi)		Assembled Lengths (ft)	Weight per Pkg. (lbs)		
		(in)	(mm)	(in)	(mm)	at 70°F (20°C)	at 122°F (50°C)		25 (ft)	50 (ft)	100 (ft)
HS1232W	12	3/4	19.1	1.080	27.4	200	120	25/50/100	6.5	12.8	25.3
HS1232W	16	1	25.4	1.360	34.5	200	120	25/50/100	9.0	17.8	35.3

NOTES:

- † Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.
- Hose assemblies are furnished with the following brass fittings: 3/4" ID – 3/4" X 3/4" MNPT, 1" ID – 1" X 1" MNPT.
 - Refer to page 56 for Technical Information.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.