



HS1317 Series

Heavy Duty PVC Water Hose Assemblies

FEATURES AND ADVANTAGES

- **Heavy Duty** – Higher working and burst pressures.
- **UV and Weather Resistant** – Opaque cover resists damage from UV light and weather aging.
- **Abrasion Resistant PVC** – Durable PVC holds up better than rubber air hoses when dragged.
- **Lightweight** – Lighter weight than rubber hoses, reduces worker fatigue.
- **Non-Marking Cover** – Can be dragged over flooring without leaving marks typical of rubber hoses.

SERVICE TEMPERATURE RANGE

+25°F (-4°C) to +150°F (+65°C)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
HS1317**



MADE IN NORTH AMERICA

Series Number	Size Code	ID		OD		Max. Working Pressure [†] (psi)		Assembled Lengths (ft)	Weight per Pkg. (lbs)
		(in)	(mm)	(in)	(mm)	at 70°F (20°C)	at 122°F (50°C)		
HS1317	12	3/4	19.1	1.025	26.0	125	50	50/100	11/22
HS1317	16	1	25.4	1.297	32.9	125	50	50/100	15/30

NOTES:

- † Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.
- 3/4" hose assemblies are furnished with heavy-duty brass GHT, 3/4" M x F fittings. 1" hose assemblies are furnished with 1" NPS pipe thread fittings.
 - Refer to page 57 for Technical Information.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.