



HS2163HDW Series

Contractor PVC Water Hose Assemblies

FEATURES AND ADVANTAGES

- **UV and Weather Resistant** – Opaque cover resists damage from UV light and weather aging.
- **Abrasion Resistant PVC** – Durable PVC holds up better than rubber air hoses when dragged.
- **Lightweight** – Lighter weight than rubber hoses, reduces worker fatigue.
- **Non-Marking Cover** – Can be dragged over flooring without leaving marks typical of rubber hoses.

SERVICE TEMPERATURE RANGE

+25°F (-4°C) to +150°F (+65°C)

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
HS2163HDW](https://KOA.link/HS2163HDW)



Series Number	Size Code	ID		OD		Max. Working Pressure [†] (psi)		Assembled Lengths (ft)	Weight per Pkg. (lbs)
		(in)	(mm)	(in)	(mm)	at 70°F (20°C)	at 122°F (50°C)		
HS2163HDW	12	3/4	19.1	1.030	26.2	150	75	50	12

NOTES:

- † Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.
- Hose assemblies are furnished with heavy-duty Brass GHT, 3/4" M x F fittings.
 - Refer to page 59 for Technical Information.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.