



K-TOUGH™
K9296 Series

High Pressure Wire & Yarn Reinforced Suction/
Discharge Hose

View Up To Date Info



◀ SCAN OR VISIT

KOA.link/
K9296



GENERAL APPLICATIONS

- Batch plants
- Constant flex applications
- Liquid chemical handling
- Mining applications (MSHA)
- Oil field water hauling
- Suction & discharge of water and slurries
- Tank trucks

CONSTRUCTION

- Tube – Clear phthalate free PVC
- Reinforcement – Galvanized steel wire helix, high tensile strength yarn reinforcement
- Cover – Blue phthalate free PVC

COMPLIANCE INFORMATION

In compliance with applicable FDA⁽⁰³⁾ requirements. Meets MSHA⁽⁰⁸⁾ and RoHS⁽¹⁴⁾ criteria

SERVICE TEMPERATURE RANGE

-5°F (-20°C) to +150°F (+65°C)

FEATURES AND ADVANTAGES

- **MSHA Accepted IC-318/02** – Cover material accepted by MSHA IC-318/02 as having met the requirements for acceptance of flame-resistant solid products taken into mines for hoses transferring air, oil, water or other fluids.
- **Steel Wire Reinforcement** – Electrogalvanized steel wire reinforcement prevents kinking and collapsing.
- **Braided Fabric Reinforcement** – High tensile strength, food grade, polyester yarn braid provides higher working pressures.
- **Increased Pressure Rating** – Heavy duty construction results in a highly durable product, designed for both indoor and demanding outdoor applications.
- **High Cycle Strength** – Designed to resist damage from constant flex applications.
- **Abrasion Resistant Cover** – Resists wear from being dragged on rough surfaces.
- **Grounding Wire** – Steel wire can be grounded to help prevent the build-up of static electricity for added safety (see below†).

Series Number	Size Code	ID (in)	ID (mm)	OD (in)	OD (mm)	Max. Working Pressure† (psi) at 70°F (20°C)	Vacuum Rating Hg (in) at 70°F (20°C)	Min. Bend Radius (in) at 70°F (20°C)	Standard Length (ft)	Approx. Weight per Pkg. (lbs)
K9296	24	1 1/2	38.1	2.030	51.6	300	29.9	5.5	50/100	45/90
K9296	32	2	50.8	2.570	65.3	275	29.9	7.0	50/100	62/124
K9296	40	2 1/2	63.5	3.070	78.0	150	29.9	9.0	50/100	79/158
K9296	48	3	76.2	3.570	90.7	150	29.9	11.0	50/100	90/180

NOTES:

† Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

CAUTION:

‡ This product is designed to dissipate static electricity when the metal wire is properly connected to ground, through the fitting or other means. Hose is not to be used in combustible situations unless it has been determined by the end user the application is not sufficient to result in propagating brush discharge.

COMPLIANCES (for details see page 91)

FDA (03), MSHA (08), Phthalate Free (13), RoHS (14)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.