



Nautilus[™]

K2W Series

Weighted Aeration Tubing

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
K2W**



GENERAL APPLICATIONS

- Commercial hatcheries
- Ice clearing
- Pond and lake aeration
- Wastewater lagoons
- Water recirculation



CONSTRUCTION

Phthalate free special black weighted PVC

SERVICE TEMPERATURE RANGE

25°F (-4°C) to +150°F (+65°C)

FEATURES AND ADVANTAGES

- **Self-Sinking** – Naturally sinks in water without the use of additional weights or anchors.
- **Easy Installation** – Greatly reduces installation time, requires no maintenance following instructions.
- **Size Options** – Available in a variety of sizes to fit most aeration systems.

Series Number	Size Code	ID		OD		Working Pressure [†] (psi) at 70°F (20°C)	Standard Length (ft)	Weight per Pkg. (lbs)
		(in)	(mm)	(in)	(mm)			
K2W	0611	3/8	9.5	0.690	17.5	50	300	60
K2W	0815	1/2	12.7	0.960	24.4	50	200	80
K2W	1017	5/8	15.9	1.065	27.1	50	100	44
K2W	1220	3/4	19.1	1.275	32.4	40	100	63
K2W	1627	1	25.4	1.690	42.9	40	100	111

NOTES:

- † Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.
- The Nautilus Weighted Aeration Tubing ID sizes and specification information listed above are based on average dimensions.
 - Special ID sizes and lengths are available on request. All products are priced on request. Check with your local sales office for additional details.

COMPLIANCES (for details see page 91)
Phthalate Free [13], **RoHS** [14]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.