



K7000 Series

Anti-Static Blasting Tubing

GENERAL APPLICATIONS

- Bulk unloading of ammonium nitrate/fuel oil blasting agents in small diameter holes
- Mining and construction site blasting
- Successfully used for years with Orica’s blast hole chargers, intermediate loaders and the Penberthy Anolader

CONSTRUCTION

Phthalate free specially-formulated anti-static PVC

SERVICE TEMPERATURE RANGE

-30°F (-35°C) to +150°F (+65°C)

View Up To Date Info



◀ SCAN OR VISIT

**KOA.link/
K7000**



MADE IN NORTH AMERICA

FEATURES AND ADVANTAGES

- **Conductivity** – Effectively limits build-up of static electricity; provides path for its safe dissipation to ground.
- **Easily Identifiable** – Co-extruded continuous orange stripe makes tubing visible in underground lighting.
- **Sufficient Resistance** – Guards blasting circuit against stray electrical currents.
- **Wear Resistance** – Smooth interior and exterior surfaces, combined with tough material formulation, provide good wear resistance.

Series Number	Size Code	Inside Diameter		Approx. OD		Max. Working Pressure† (psi) at 70°F (20°C)		Standard Length		Weight per 100 (ft) (lbs)	Weight per 100 (m) (kg)
		(in)	(mm)	(in)	(mm)	(psi)	(MPa)	(ft)	(m)		
K7000	10	5/8	16	0.859	22	120	0.83	200	61	17.5	25
K7000	12	3/4	19	1.063	27	120	0.83	200	61	28.0	40
K7000	16	1	25	1.328	34	120	0.83	300	91	38.0	55
K7000	20	1 1/4	32	1.625	41	120	0.83	100	30	55.0	78

NOTES:

† Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

COMPLIANCES (for details see page 91)
Phthalate Free [13]

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.