

COMPARISON

		NEW		UPDATED
				
	KC1-H83	KC3-H83	KC1-H130	KC3-H130
Crimping Force (ton)	150	198	210	210
Max. Capacity 1-2 Wire Braided (in)	1 1/2	1 1/2	2	2
Max. Capacity 4 Spiral (in)	1 1/4	1 1/4	2	2
Max. Capacity 6 Spiral (in)	1	1	1 1/4	1 1/2*
Max. Capacity Industrial (in)	1 1/2	1 1/2	3	3
Max. Opening without Dies (mm / in)	111 / 4.37	111 / 4.37	154 / 6.06	154 / 6.06
Max. Opening with Dies (mm / in)	96 / 3.78	96 / 3.78	108 / 4.25	108 / 4.25
Power	4.0 HP (230 V)	5.0 HP (230 V)	2.9 HP (230 V)	5.5 HP (230 V)
Page Number	15	16	17	18

* Limited to intermittent use with 5,000 PSI Alfagomma hose using 1-pc fittings

		UPDATED	UPDATED	UPDATED
				
	KC1-H135	KC3-H135	KC3-H144	KC3-H170
Crimping Force (ton)	330	345	440	308
Max. Capacity 1-2 Wire Braided (in)	2	2	2 1/2	2
Max. Capacity 4 Spiral (in)	2	2	2 1/2	2
Max. Capacity 6 Spiral (in)	2	2	2	2*
Max. Capacity Industrial (in)	3	3	4	4†
Max. Opening without Dies (mm / in)	162 / 6.38	162 / 6.38	203 / 7.99	219 / 8.62
Max. Opening with Dies (mm / in)	139 / 5.47	139 / 5.47	176 / 6.93	192 / 7.56
Power	7.5 HP** (230 V)	7.5 HP (230 V)	7.5 HP (230 V)	7 HP (230 V)
Page Number	19	20	21	22

* Limited to 5,000 PSI Alfagomma hose using 1-pc fittings

** 5.5 HP for single phase

† Up to 5" depending on hose and coupling type

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.