

KC3-H130 Series

UPDATED



DESCRIPTION

The production oriented KC3-H130 takes a step up in size capabilities, with the ability to crimp 2" wire braid and 4 SP hydraulic hose, as well as 1 1/2" 5,000 PSI 6 SP hydraulic hose intermittently. The new intuitive MACH interface improves efficiency and reduces crimp cycle times.

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
KC3-H130](http://KOA.link/KC3-H130)

INCLUDED ACCESSORIES



Electric Foot Pedal
PEDAL-ES



Crimp Calculator



Die Segment
Change Tool


OPTIONAL ACCESSORIES (PGS. 41 – 48)



Quick Change
Die Tool
KCQCT-H119



Production Quick
Change Die Tool
KCPQCT-H135



Die Holder Base
(18 pc.)
DIEBASE-H119



Die Rack (8 pc.)
DIERACK-H119




Back Limit Switch



Cleaning and
Lubrication Kit
CALKIT-H130



Custom Made Dies



Back Mirror
MIRROR-H130



Marking Dies

i Refer to pg. 23 for available dies

Hose Capacity (in)	Crimping Force (ton)
1 – 2 Wire	2
4 SP / 6 SP	2 / 1 1/2*
90° Fittings	2
Industrial	3

210

*1 1/2" limited to intermittent use with 5,000 PSI hose & 1-pc fittings

Opening Diameter	
Max. Without Dies (mm / in)	154 / 6.06
Max. With Dies (mm / in)	108 / 4.25
By Die Size (mm / in)	Die Size + 35 / 1.38

Crimper Size	
L x W x H (in)	29.9 x 27.1 x 28.7
Weight (lbs)	650

Part Number	Motor Info
KC3-H130-230/1	5.5 HP (230 V) 1 PH
KC3-H130-230/3	5.5 HP (230 V) 3 PH

Die Series	Die Range (mm)
H119	6 – 96

Hydraulic Fluid	
Type	ISO 46
Amount	65L = 17.18 Gal.

CONTROL MECHANISM **NEW**



MACH

- Full-color, touch-screen display
- Stores up to 1000 crimp specifications
- Built-in crimp diameter calculator
- Adjustable reopen diameter
- USB port option for data transfer
- Industrial hose crimp calculator

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.