

KCS-TF3/E Series



DESCRIPTION


A stand alone unit ideal for cutting 2" four spiral and six spiral hydraulic hose. The blade is recessed inside the base for additional safety.

Suggested for use with KC1-H135 series crimpers.


INCLUDED ACCESSORIES



Recessed Blade



Ventilation Port*



Serrated Blade†
BLADE-SER250

* Separate suction device required for fume extraction

† CAUTION: The included Serrated Blade is not recommended for use with hoses with a steel cover and/or containing steel helical reinforcement.

Hose Capacity (in)		Motor Strength (HP)
1 – 2 Wire	2	4
4 SP / 6 SP	2 / 2	
Industrial	2 1/2	
Max opening (mm)	85	
Cutter Size		
L x W x H (in)	30.0 x 20.9 x 20.1	
Weight (lbs)	130	
Blade Diameter (mm)	350	
Part Number		Motor Info
KCS-TF3/E-230/1		4 HP (230 V) 1 PH
KCS-TF3/E-230/3		4 HP (230 V) 3 PH

View Up To Date Info




◀ SCAN OR VISIT
[KOA.link/
KCS-TF3-E](https://KOA.link/KCS-TF3-E)

OPTIONAL ACCESSORIES



Centering &
Measuring Device
CENTER-KCS



Smooth Blade
BLADE-SMT250



Diamond Blade
BLADE-DIA250

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.