

KCS-TF3 Series



Hose Capacity (in)		Motor Strength (HP)
1 – 2 Wire	3	7.5
4 SP / 6 SP	2 1/2 / 2	
Industrial	2 1/2	
Max opening (mm)	100	

Cutter Size	
L x W x H (in)	39.4 x 28.0 x 45.3
Weight (lbs)	419
Blade Diameter (mm)	400

Part Number	Motor Info
KCS-TF3-230/3	7.5 HP (230 V) 3 PH

DESCRIPTION

A stand alone unit ideal for cutting 3" two wire hose and 2" six spiral hydraulic hose. The blade is recessed inside the base for additional safety.

Suggested for use with KC3-H135 series crimpers.

View Up To Date Info



◀ SCAN OR VISIT


KOA.link/

KCS-TF3-2303

INCLUDED ACCESSORIES



Enclosed Blade Chamber



Ventilation Port*



Serrated Blade†
BLADE-SER250


* Separate suction device required for fume extraction

† CAUTION: The included Serrated Blade is not recommended for use with hoses with a steel cover and/or containing steel helical reinforcement

OPTIONAL ACCESSORIES




Centering & Measuring Device
CENTER-KCS



Measuring Hose Tray
TRAY-KCS



Stroke Counter
STROKE-KCS



Smooth Blade
BLADE-SMT250



Diamond Blade
BLADE-DIA250

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.