

## KCS-TF3/PI Series



Hose Capacity (in)		Motor Strength (HP)
1 – 2 Wire	3	7.5
4 SP / 6 SP	2 1/2 / 2	
Industrial	2 1/2	
Max opening (mm)	100	
Cutter Size		
L x W x H (in)	40.4 x 27.6 x 45.3	
Weight (lbs)	530	
Blade Diameter (mm)	400	
Part Number		Motor Info
KCS-TF3/PI-230/3		7.5 HP (230 V) 3 PH

### DESCRIPTION

A stand alone unit ideal for cutting 2" six spiral hydraulic hose. The blade is recessed inside the base for additional safety. Uses 100 PSI pneumatic input control.

Suggested for use with KC3-H135 series crimpers.

View Up To Date Info



◀ SCAN OR VISIT


[KOA.link/](https://KOA.link/)

**KCS-TF3-PI-2303**


### INCLUDED ACCESSORIES



Enclosed Blade Chamber



Ventilation Port\*



Serrated Blade†  
BLADE-SER250


\* Separate suction device required for fume extraction

† CAUTION: The included Serrated Blade is not recommended for use with hoses with a steel cover and/or containing steel helical reinforcement

### OPTIONAL ACCESSORIES



Centering &  
Measuring Device  
CENTER-KCS



Measuring Hose Tray  
TRAY-KCS



Stroke Counter  
STROKE-KCS



Smooth Blade  
BLADE-SMT250



Diamond Blade  
BLADE-DIA250

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.