

COMPARISON

BENCH MOUNTED



	KCS-TT30PI	KCS-TF1D/E-BAT	KCS-TF1/E	KCS-TF2/E	KCS-TF3/E	KCS-TF4/E
Max. Capacity 1-2 Wire (in)	NA	1 1/4	1 1/4	2	2	3
Max. Capacity 4 Spiral (in)	NA	1 1/4	1 1/4	2	2	3
Max. Capacity 6 Spiral (in)	NA	1	1	1 1/2	2	2
Max. Capacity Industrial (in)	5/8	1 1/2	2	2	2 1/2	4
Max. Opening (mm / in)	30 / 1.18	55 / 2.16	60 / 2.36	75 / 2.95	85 / 3.35	130 / 5.12
Blade Diameter (mm)	NA	165	250	250	350	400
Power	87 (PSI)	18V	1.5 HP (110 V)	4.0 HP (230 V)	4.0 HP (230 V)	5.5 HP (230 V)
Page Number	58	59	60	61	62	63

STAND ALONE



	KCS-TF2	KCS-TF3	KCS-TF3/PI	KCS-TF4	KCS-TF5DI	KCS-TF6	KCS-TFIH10
Max. Capacity 1-2 Wire (in)	2	3	3	3	3	3	NA
Max. Capacity 4 Spiral (in)	2	2 1/2	2 1/2	2 1/2	2 1/2	3	NA
Max. Capacity 6 Spiral (in)	1 1/2	2	2	2	2 1/2	3	NA
Max. Capacity Industrial (in)	2	2 1/2	2 1/2	3	5*	4	10*
Max. Opening (mm / in)	75 / 2.95	100 / 3.94	100 / 3.94	100 / 3.94	160 / 6.30	160 / 6.30	NA
Blade Diameter (mm)	250	400	400	400	520	650	NA
Power	4 HP (110 V)	7.5 HP (230 V)	7.5 HP (230 V)	7.5 HP (230 V)	10.0 HP (230 V)	15 HP (230 V)	1.22 HP (230 V)
Powered Foot Pedal	No	No	Yes	Yes	Yes	Yes	No
Low Smoke Emission	No	No	No	Yes	Yes	Yes	No
Page Number	64	65	66	67	68	69	70

* Dependent on hose type

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.