

6 - 46

70L = 18.50 Gal.

## KC4-V59 Series







**⟨** SCAN OR VISIT KOA.link/ KC4-V159

Hose Capacity (in)		Crimping Force (ton)
1 – 2 Wire	1 1/2	
4 SP / 6 SP	1 1/4 / 1	155
90° Fittings	1 1/2	<b>155</b>
Industrial	NA	

Opening Diameter			
Max. Without Dies (mm / in)	119 / 4.69		
Max. With Dies (mm / in)	96 / 3.78		
By Die Size (mm / in)	Die Size + <b>50 / 1.97</b>		

Crimper Size	
LxWxH(in)	25.9 x 28.3 x 58.6
Weight (lbs)	1,199

Part Number	Motor Info	
KC4-V59-230/3	7.5 HP (230 V) 3 PH	
Die Series	Die Range (mm)	

Hydraulic Fluid	
Туре	ISO 46

#### **CONTROL MECHANISM**



ES4

V69

Amount

- Large, full-color, touch-screen display
- Stores up to 1,000 crimp specifications
- Built-in crimp diameter calculator
- USB port connection
- · Optional upgrades such as digital caliper, history data save, barcode reader, webcam and WiFi connection

### **DESCRIPTION**

A mass production crimper boasting an impressive 3,900\* crimps per hour. Its back limit switch and advanced Siemen's ES4 computerized controller take efficiency to the highest level. The crimping chamber is fixed at the 6 o'clock position allowing the hose to rest inside the chamber rather than having to be centered.

#### **INCLUDED ACCESSORIES**







Die Holder Base (12 pc.)



**Fitting Orientation** Protractor



Crimp Calculator

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



<sup>\*</sup>Theoretical with a 1/2"  $\triangle$  @ 6mm hose



# KC4-V59 Series

### OPTIONAL ACCESSORIES (PGS. 41 - 48)















Production Quick Change Die Tool KCPQCT-V59

ES4 Upgrades (pgs. 43-44)

**Custom Made Dies** 

Marking Dies

Mounted Side Ta TABLE-KC

Mounted Side Table Back Limit Switch

Back Mirro

## **KCDV Series**

### Available Dies for KC4-V59

Die Number	Crimp Range (mm)	Closed Diameter (mm)	Length (mm)	Weight (lbs/ea)
KCDV69-6	6.0 - 8.0	6	85	4.0
KCDV69-8	8.0 - 10.0	8	85	4.0
KCDV69-10	10.0 - 12.0	10	85	4.0
KCDV69-12	12.0 - 14.0	12	85	4.0
KCDV69-14	14.0 - 16.0	14	85	4.0
KCDV69-16	16.0 - 19.0	16	85	4.0
KCDV69-19	19.0 - 22.0	19	85	4.0
KCDV69-22	22.0 - 25.0	22	85	4.0
KCDV69-25	25.0 - 29.0	25	85	4.0
KCDV69-29	29.0 - 34.0	29	85	4.0
KCDV69-34	34.0 - 38.0	34	85	4.0
KCDV69-38	38.0 - 42.0	38	85	4.0
KCDV69-42	42.0 - 46.0	42	85	4.0
KCDV69-46	46.0 - 50.0	46	85	4.0
KCDV69-50	50.0 - 54.0	50	85	4.0

Special dies available up to 54 mm.

