

COMPARISON


KC4-V59

KC4-V150

KC4-V159

KC4-V160

Crimping Force (ton)	155	340	330	386
Max. Capacity 1-2 Wire Braided (in)	1 1/2	2 1/2	2 1/2	3
Max. Capacity 4 Spiral (in)	1 1/4	2 1/2	2 1/2	3
Max. Capacity 6 Spiral (in)	1	2 1/2	2 1/2	3
Max. Capacity Industrial (in)	NA	4	5*	6
Max. Opening without Dies (mm / in)	119 / 4.69	189 / 7.44	228 / 8.98	288 / 11.34
Max. Opening with Dies (mm / in)	96 / 3.78	166 / 6.35	201 / 7.91	261 / 10.28
Power	7.5 HP (230 V)	7 HP (230 V)	7.5 HP (230 V)	10 HP (230 V)
Page Number	24-25	26, 29	27, 29	28-29

* up to 6" (depending on hose and coupling type)


KC4-V250

KC4-V300

KC4-V450

Crimping Force (ton)	551	725	728
Max. Capacity 1-2 Wire Braided (in)	3	3	3
Max. Capacity 4 Spiral (in)	3	3	3
Max. Capacity 6 Spiral (in)	3	3	3
Max. Capacity Industrial (in)	10	12	16
Max. Opening without Dies (mm / in)	15 HP (230 V)	10 HP (230 V)	10 HP (230 V)
Max. Opening with Dies (mm / in)	380 / 14.96	475 / 18.70	560 / 22.05
Power	340 / 13.39	345 / 13.58	530 / 20.80
Page Number	30-31	32-33	34-35

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.