



ST6D2AA Series 400 PSI Oil Rigger/Frack Discharge Hose with SUPERTUFF Cover

General Applications:

Fracking fluids, liquid mud and crude oil delivery in heavy duty oil field and gas exploration.

Construction:

Tube: Black synthetic elastomer.

Reinforcement: High tensile textile cords.

Cover: Black SUPERTUFF cover – abrasion, oil and ozone resistant.

Working Pressure:

Constant Pressure – 27 Bar (400 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY OIL RIGGER – FRACK 27 BAR (400 PSI) (in blue letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
ST6D2AA400	4	102	4.72	120	400	100	2.93

COUPLING SUGGESTIONS

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.