



T766AA Series 150 PSI Heavy Duty Dry Powder Delivery Hose

General Applications:

Discharge of dry powders in heavy duty applications, such as dry cement, grains and animal feed transfer.

Construction:

Tube: 1/4" black static conducting NR – compounded to resist cutting by abrasive materials.

Reinforcement: Spiraled high tensile textile cords.

Cover: Black conductive SBR/NR blend – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T766 10 Bar (150 PSI)
BULK MATERIAL DELIVERY (in white letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T766AA400	4	102	4.65	118	150	100	1.96

★ Excessive bending during operation may cause premature wear.

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.