



## T340AA/AH Series 270 PSI EPDM Braided Steam Hose Assemblies

### GENERAL APPLICATIONS

- Saturated steam applications up to 270 PSI and 410°F
- High pressure industrial equipment cleaning at refineries, processing plants and shipyards
- Thawing and de-icing of outdoor pipes and other equipment during cold temperatures

### CONSTRUCTION

**Tube** – Black, conductive EPDM.

**Reinforcement** – Single high tensile steel wire braid (1/2" Size), Two high tensile steel wire braids (3/4" to 3").

**Cover** – Red or black pin-pricked EPDM.

**Ends** – Crimped on male NPT x female ground joint with NPT spud.

### SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +410°F (+210°C)

### FEATURES AND ADVANTGES

- **Crimped on Fittings** – The preferred connection method. Reduces risk of leaks and blowouts versus bolt clamps, which require repeated tightening in order to maintain a tight seal.

VIEW ONLINE



SCAN FOR INFO  
or visit  
[KOA.link/  
Steam-Assemblies](http://KOA.link/Steam-Assemblies)

Series Number	Color	ID (in)	ID (mm)	Max. Rec.* WP (psi)	Min. Bending Radius at 68°F (in)	Fitting Types	Length (ft)	Weight (lbs/each)
T340AA050MPMPX50	black	1/2	13	270	5	Male NPT x Male NPT	50	14.11
T340AA075GFGFX50	black	3/4	19	270	7 1/2	Female GJ x Female GJ	50	33.51
T340AA075GFMPX25	black	3/4	19	270	7 1/2	Male NPT x Female GJ	25	12.60
T340AH075GFMPX25	red	3/4	19	270	7 1/2	Male NPT x Female GJ	25	12.60
T340AA075GFMPX50	black	3/4	19	270	7 1/2	Male NPT x Female GJ	50	25.10
T340AH075GFMPX50	red	3/4	19	270	7 1/2	Male NPT x Female GJ	50	25.40
T340AA075MPMPX50	black	3/4	19	270	7 1/2	Male NPT x Male NPT	50	26.01
T340AA100GFGFX50	black	1	25	270	10	Female GJ x Female GJ	50	38.14
T340AA100GFMPX25	black	1	25	270	10	Male NPT x Female GJ	25	15.40
T340AH100GFMPX25	red	1	25	270	10	Male NPT x Female GJ	25	15.50
T340AA100GFNPX50	black	1	25	270	10	Male NPT x Female GJ	50	30.60
T340AH100GFMPX50	red	1	25	270	10	Male NPT x Female GJ	50	31.10
T340AA100MPMPX50	black	1	25	270	10	Male NPT x Male NPT	50	32.41
T340AA200GFMPX25	black	2	51	270	20	Male NPT x Female GJ	25	40.34
T340AA200GFMPX50	black	2	51	270	20	Male NPT x Female GJ	50	76.06

\*10:1 Safety Factor

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.