

# Kuri Tec<sup>®</sup>

## **KLEARON<sup>™</sup> 68 K018 Series Clear PVC Tubing**

Clear Phthalate Free PVC food grade tubing for applications requiring more flexibility.

#### **Construction:**

Crystal clear Phthalate Free PVC compound, formulated with ingredients in compliance with applicable FDA<sup>(03)</sup>, RoHS<sup>(16)</sup> and USP<sup>(19)</sup> Class VI requirements.

#### Features:

- · High gloss.
- Blue tint.
- Food grade clear PVC tubing.
- Self-extinguishing.
- Compound hardness 68±3 Shore "A".
- Phthalate Free!

Service Temperature Range: +25°F (-4°C) to +150°F (+65°C)

**Applications:** 

Tubing for laboratories.

• Water, air, drainage lines.

Ideal for medical applications requiring USP class VI.

Similar to K010 applications in which a slightly more

• Beverage dispensing & ice making applications.

flexible tube is desired by the customer.

Water transfer, purification systems.

Nominal Specifications										
Series No.	Size Code	Nominal ID		Nominal OD		Nominal Wall		Working Pressure† (PSI)	Standard Length	Approx. Wt. per
		(In)	(mm)	(In)	(mm)	(In)	(mm)	@70°F (20°C)	Ctn/Coils	Pkg.
K018	0204	1/8	3.2	1/4	6.4	1/16	1.6	65	100 ft.	2.0 lbs.
K018	0305	3/16	4.8	5/16	7.9	1/16	1.6	55	100 ft.	2.7 lbs.
K018	0306	3/16	4.8	3/8	9.5	3/32	2.4	60	100 ft.	4.5 lbs.
K018	0406	1/4	6.4	3/8	9.5	1/16	1.6	55	100 ft.	3.4 lbs.
K018	0407	1/4	6.4	7/16	11.1	3/32	2.4	58	100 ft.	5.5 lbs.
K018	0507	5/16	7.9	7/16	11.1	1/16	1.6	50	100 ft.	4.0 lbs.
K018	0508	5/16	7.9	1/2	12.7	3/32	2.4	55	100 ft.	6.5 lbs.
K018	0608	3/8	9.5	1/2	12.7	1/16	1.6	45	100 ft.	4.7 lbs.
K018	0609	3/8	9.5	9/16	14.3	3/32	2.4	50	100 ft.	7.5 lbs.
K018	0709	7/16	11.1	9/16	14.3	1/16	1.6	35	100 ft.	5.3 lbs.
K018	0810	1/2	12.7	5/8	15.9	1/16	1.6	30	100 ft.	6.0 lbs.
K018	1013	5/8	15.9	13/16	20.6	3/32	2.4	35	100 ft.	11.6 lbs.

\* Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures. Use of compression fittings with Kuri Tec® non-reinforced PVC tubing is not recommended. Hose claims involving use of these fittings will be disallowed.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

### FDA<sup>(03)</sup>, Phthalate Free<sup>(15)</sup>, RoHS<sup>(16)</sup>, USP<sup>(19)</sup>

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS. WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.