

NEW



MNTR Series

500 PSI Air and Multipurpose Hose

GENERAL APPLICATIONS

- Air hammer
- Heavy construction
- Mining
- Petroleum transfer
- Quarry operations
- Rock drilling
- Washdown
- Water jetting



CONSTRUCTION

- **Tube** – Nitrile (NBR), meeting ARPM Class A (High Oil Resistance).
- **Reinforcement** – 4-Spiral polyester yarn.
- **Cover** – Carboxylated Nitrile (XNBR), meeting ARPM Class A (High Oil resistance). MSHA approved.

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +212°F (+100°C)

BRANDING

 Kuriyama Minotaur 500  MNTR - ____ Size I.D. 500 PSI MSHA 1C-114/1 Made In USA

VIEW ONLINE



SCAN FOR INFO

or visit

KOA.link/MNTR



FEATURES AND ADVANTAGES

- **Superior Abrasion Resistance** – Carboxylated nitrile rubber cover provides greater abrasion resistance than standard nitrile for demanding applications.
- **Flame Resistant Cover** – MSHA approved for acceptance of products to be used in underground mines (No. 1C-114/1).
- **Oil Resistant Tube** – Meets APRM Class A (High Oil Resistance) Rating, for use with gasoline, diesel, bio-diesel and kerosene.
- **Non-conductive[^]** – Helps protect user from shock when used near high-voltage sources.
- **Safety Yellow Cover** – High visibility, florescent yellow cover reduces risk of running or tripping over hose.

Part Number	ID		OD		Working Pressure (psi) [†]	Reel Length* (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
MNTR-050x500	1/2	12.7	0.91	23.0	500	500	0.24
MNTR-075x500	3/4	19.1	1.19	30.2	500	500	0.36
MNTR-100x500	1	25.4	1.50	38.1	500	500	0.51
MNTR-125x400	1 1/4	31.75	1.75	44.5	500	400	0.66

*Maximum two pieces per reel

[^] Meets a minimum of 1,000,000 ohms per inch resistance when tested with a 1,000-volt D.C. megger.

[†] 4:1 safety factor

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.