# **Kuriyama Oilfield Couplings & Gaskets**

## **AL-LDHC Series**Oilfield Hose Coupling

- Lightweight aluminum with abrasion resistant anodized hard coating
- Mulitple collar segments evenly distribute pressure on the hose for even sealing
- Locking Lip<sup>™</sup> provides better coupling rentention than other designs

Don't risk a leak! , Unique Locking Lip™ design increases coupling retention.





Nominal Specifications					
Part Number	Size	Working Pressure		Weight Each	Stand

r art Hambon	(in)	(psi) at 68°F	(psi) at 68°F	(lbs)	Carton
AL-LDHC1000	10	200	600	41.20	1
AL-LDHC1200	12	200	600	57.30	1

#### **GEC-B Series**

#### **Grooved Couplings**

- For use with AL-LDHC coupling or grooved end pipe
- Durable ductile iron
- UL listed
- Buna (nitrile) gasket included

Nominal Specifications				
Part Number	Size (in)	Weight Each (lbs)	Standard Carton	
GEC-B1000	10	26.15	1	
GEC-B1200	12	30.65	1	



### **GEB-Buna Grooved Gasket**

#### • Fits GEC-B Series couplings

 Buna (nitrile) material, resistant to oil, gas, and moderately aggressive chemicals

Nominal Specifications				
Part Number	Size (in)	Weight Each (lbs)	Standard Carton	
GEG-BUNA1000	10	0.771	1	
GEG-BUNA1200	12	0.889	1	



Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.